

View Online at <https://aerobasegroup.com/nsn/5945-00-793-1952>

Thread Class:

2a mounting facility stud

Thread Direction:

Right-hand mounting facility stud

Body Style:

Base end actuator

Body Diameter:

Between 1.822 inches and 1.953 inches

Body Height:

Between 1.090 inches and 1.100 inches

Case Material:

Steel

Case Surface Treatment:

Cadmium

Environmental Protection:

Any acceptable

Connector Manufacturer Code:

18876

Connector Manufacturer Part Number:

9155718

Maximum Operating Temp:

85.0 degrees celsius

Fragility Factor:

Moderately rugged

Actuator Diameter:

Between 0.249 inches and 0.251 inches

Inclosure Type:

Fully enclosed

Magnetic Coil Quantity:

1

Electrical Resistance:

3.20 ohms

Duty Type:

Continuous

Terminal Location:

Circumference

Voltage Rating In Volts:

28.0 ac

Mounting Facility Type And Quantity:

1 threaded stud

Current Rating:

1.8 amperes

Storage Type:

General purpose warehouse

Cubic Measure:

3.539 cubic inches

Thready Qty Per Inch (tpi):

32 mounting facility stud

Actuator Stroke Type:

Rotary

Power Takeoff Connection Type:

Plain-drilled

Thread Size:

0.164 inches mounting facility stud

Mounting Facility Pattern:

Single position

Rotation Direction And Energizing Stroke In Angular Deg:

90.0 counterclockwise

Thread Series Designator:

Unc mounting facility stud

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A134a0