

NSN 5945-00-799-3303 AC
Electromagnetic Relay - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5945-00-799-3303
Thread Class:
2b single mounting facility
Overall Length:
2.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.688 inches single mounting facility
Overall Height:
1.875 inches
Overall Width:
1.031 inches
Environmental Protection:
Dust tight
Contact Material:
Silver
Contact Surface Treatment:
Gold flash
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
778.0 ohms single winding
Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

12c

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Operating Current Rating And Type:

62.0 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

NSN 5945-00-799-3303

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contact and terminal surface silver and contact surface gold

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

38 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300