

| NSN 5945-00-799-3303 AC |
|---|
| Electromagnetic Relay - Page 1 of 2 |
| View Online at https://aerobasegroup.com/nsn/5945-00-799-3303 |
| |
| Thread Class: |
| 2b single mounting facility |
| Overall Length: |
| 2.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.688 inches single mounting facility |
| Overall Height: |
| 1.875 inches |
| Overall Width: |
| 1.031 inches |
| Environmental Protection: |
| Dust tight |
| Contact Material: |
| Silver |
| Contact Surface Treatment: |
| Gold flash |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 778.0 ohms single winding |
| Duty Type: |

Continuous

Mounting Facility Type And Quantity:

2 threaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

12c

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

In-line single mounting facility

Operating Current Rating And Type:

62.0 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

48.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

NSN 5945-00-799-3303

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contact and terminal surface silver and contact surface gold

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

38 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300