NSN 5945-00-803-4585

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-803-4585

| view Online at https://aerobasegroup.com/hsn/5945-00-805-4565 |
|--|
| Overall Length: |
| 2.190 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.812 inches single mounting facility |
| Overall Height: |
| 4.781 inches |
| Overall Width: |
| 1.520 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.173 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 2.000 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 131.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 210.0 milliamperes dc single winding |
| Time Delay: |
| 0.75 seconds adjustable release time and 10.00 seconds adjustable release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |

5.0 amperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

240.0 ac and 110.0 dc

Terminal Type And Quantity:

8 tab, solder lug all functions

Shelf Life:

N/a

NSN 5945-00-803-4585

Electromagnetic Relay - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A03300