NSN 5945-00-804-4753

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-804-4753

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 2.430 inches |
| Overall Height: |
| 1.430 inches |
| Overall Width: |
| 1.650 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 9.1 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Features Provided: |
| Polarized |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Operating Current Rating And Type: |
| 8.0 milliamperes dc single winding |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.187 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 72.8 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes ac resistive load and 3.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| |
| 115.0 ac and 26.5 dc |

Unc single mounting facility

NSN 5945-00-804-4753

Electromagnetic Relay - Page 2 of 2



| Terminal ' | Type And | Quantity: |
|--------------|------------|------------|
| ı errillinar | I VDE AIIU | Qualitity. |

4 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300