

View Online at <https://aerobasegroup.com/nsn/5945-00-804-9409>

**Thread Class:**

2b single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

1.156 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.438 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.375 inches single mounting facility

**Overall Height:**

1.062 inches

**Overall Width:**

0.688 inches

**Case Material:**

Steel, corrosion resisting

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**Contact Material:**

Silver

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

300.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 threaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

0.844 cubic inches

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.015 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

27.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

8 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300