NSN 5945-00-807-3360

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-807-3360 **Thread Class:** 2a mounting facility stud **Body Style:** Base end actuator **Center To Center Distance Between Mounting Facilities Parallel To Width:** 1.250 inches **Body Diameter:** 1.875 inches **Body Height:** 1.203 inches **Case Material:** Steel **Case Surface Treatment:** Zinc **Actuator Diameter:** Between 0.250 inches and 0.251 inches **Inclosure Type:** Fully enclosed **Magnetic Coil Quantity: Electrical Resistance:**

986.00 ohms

Duty Type:

Continuous

Terminal Location:

Circumference

Voltage Rating In Volts:

150.0 dc

Mounting Facility Type And Quantity:

2 threaded stud

Torque Rating And Type:

2.60 inch-pounds starting and 4.41 inch-pounds end

Thready Qty Per Inch (tpi):

32 mounting facility stud

Actuator Stroke Type:

Rotary

Power Takeoff Connection Type:

Plain

Thread Size:

0.164 inches mounting facility stud

Mounting Facility Pattern:

Two position in-line

NSN 5945-00-807-3360

Electrical Solenoid - Page 2 of 2



Rotation Direction	And Energizing	Stroke In	Angular	Deg:
25.0 clockwise				

Special Features:

Surface treatment document and classification: baqq-z-325, type 1, class 3

Surface Treatment Specification:

Qq-z-325, type 1, class 3 federal specification single treatment response

Thread Series Designator:

Unc mounting facility stud

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A134a0