NSN 5945-00-810-1067

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-810-1067

Thread Class:

2a single mounting facility

Overall Length:

1.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.984 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.984 inches single mounting facility

Overall Height:

1.968 inches

Overall Width:

1.000 inches

Environmental Protection:

Hermetic

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

8.0 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Current Rating And Type:

16.0 milliamperes dc single winding

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

5 pin all functions

NSN 5945-00-810-1067

Electromagnetic Relay - Page 2 of 2



Reference	Number	Differentiating	Characteristics:
11010101100	HUIIDEI	Differentiation	Ullai actel istics.

As differentiated by coil quantity, winding and operating voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300