

View Online at <https://aerobasegroup.com/nsn/5945-00-810-2974>

**Overall Length:**

2.187 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.844 inches single mounting facility

**Overall Height:**

2.156 inches

**Overall Width:**

1.031 inches

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.147 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Frequency In Hertz:**

400.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

Specific

**Coil Quantity:**

1

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

2 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

4.543 cubic inches

**Mounting Facility Pattern:**

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Operating Current Rating And Type:**

70.0 milliamperes ac single winding

**Time Delay:**

0.05 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 pin all functions

**Specification Data:**

96906-ms25323 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300

**Mil-std (military Standard):**

Mil-r-6106 spec.