NSN 5945-00-810-6808

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-810-6808

| Overall Length: |
|---|
| 2.590 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches single mounting facility |
| Overall Height: |
| 1.500 inches |
| Overall Width: |
| 1.810 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.156 inches single mounting facility |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 2.35 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 20.0 milliamperes dc single winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 230.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 13.0 amperes ac resistive load and 250.0 milliamperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 115.0 dc |
| Terminal Type And Quantity: |
| 8 tab, solder lug all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5945-00-810-6808

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300