## NSN 5945-00-813-9709

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-813-9709

**Thread Class:** 

2a single mounting facility

**Thread Direction:** 

Right-hand single mounting facility

**Overall Length:** 

1.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.557 inches single mounting facility and 1.567 inches single mounting facility

**Overall Height:** 

2.343 inches

**Overall Width:** 

1.312 inches

**Environmental Protection:** 

Hermetic and shock resistant and vibration resistant

Winding Quantity:

1

**Coil Quantity:** 

Winding Dc Resistance Rating:

400.0 ohms single winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

2 threaded stud single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.164 inches single mounting facility

**Mounting Facility Pattern:** 

In-line single mounting facility

**Nonpile-up Main Contact Arrangement:** 

6 pole, double throw, one position momentary

Time Delay:

0.025 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

40.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

26.5 dc

**Precious Material And Location:** 

Terminal surfaces gold and terminal surfaces silver

## NSN 5945-00-813-9709

Electromagnetic Relay - Page 2 of 2



Precious Material:
Gold and silver
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
20 pin all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A03300