NSN 5945-00-815-1050

Electromagnetic Relay - Page 1 of 2

6 pin all functions



View Online at https://aerobasegroup.com/nsn/5945-00-815-1050

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 2.400 inches |
| Overall Height: |
| 1.400 inches |
| Overall Width: |
| 1.620 inches |
| Environmental Protection: |
| Hermetic |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 450.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 1a1b |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Operating Current Rating And Type: |
| 250.0 milliamperes ac single winding |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.187 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |

NSN 5945-00-815-1050

Electromagnetic Relay - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300