

View Online at <https://aerobasegroup.com/nsn/5945-00-816-1627>

**Overall Length:**

3.218 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.611 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.375 inches single mounting facility

**Overall Height:**

2.310 inches

**Overall Width:**

1.827 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches single mounting facility

**Fragility Factor:**

Moderately rugged

**Contact Material:**

Silver

**Frequency In Hertz:**

Between 50.0 and 60.0

**Winding Quantity:**

2

**Purpose For Which Designed:**

General

**Coil Quantity:**

2

**Winding Dc Resistance Rating:**

1.03 kilohms all windings

**Duty Type:**

Intermittent

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Latching contacts

**Cubic Measure:**

13.581 cubic inches

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Operating Current Rating And Type:**

44.0 milliamperes ac all windings

**Time Delay:**

0.025 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

120.0 volts ac 25 degrees celsius all windings

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Energizing Element Power Rating:**

5.0 volts-amperes

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

16 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300