

View Online at <https://aerobasegroup.com/nsn/5945-00-822-1345>

Overall Length:

6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.125 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.875 inches single mounting facility

Overall Height:

3.312 inches

Overall Width:

4.453 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.218 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

2

Purpose For Which Designed:

General

Coil Quantity:

2

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

88.490 cubic inches

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, double make, momentary action

Time Delay:

0.01 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

50.0 amperes ac resistive load and 50.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

12 threaded stud all functions

Specification Data:

96906-ms24153 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.