NSN 5945-00-822-3219

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-822-3219

Overall Length:

1.870 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.406 inches single mounting facility

Overall Diameter:

1.000 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.147 inches single mounting facility

Frequency In Hertz:

Between 60.0 and 400.0

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

300.0 ohms first winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Features Provided:

Latching contacts

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Operating Current Rating And Type:

 $60.0 \ \mbox{milliamperes}$ ac all windings and $50.0 \ \mbox{milliamperes}$ dc all windings

Time Delay:

0.01 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

18.0 volts ac 25 degrees celsius all windings and 18.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 28.0 dc

Terminal Type And Quantity:

7 pin all functions

Shelf Life:

N/a

NSN 5945-00-822-3219

Electromagnetic Relay - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300