# NSN 5945-00-823-3056

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-823-3056

#### **Thread Class:**

2a single mounting facility

#### **Overall Length:**

0.800 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.488 inches single mounting facility

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

0.220 inches single mounting facility

#### **Overall Height:**

0.926 inches

#### **Overall Width:**

0.400 inches

**Environmental Protection:** 

#### Hermetic

Winding Quantity:

# Coil Quantity:

1

1

# Winding Dc Resistance Rating:

4.5 kilohms single winding

## Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

#### **Thread Size:**

0.112 inches single mounting facility

#### Mounting Facility Pattern:

Diagonal single mounting facility

# Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### Time Delay:

0.006 seconds fixed operate and release time

#### **Operating Voltage Rating And Type At Specificationified Temp:**

78.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

# Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 32.0 dc

#### **Thread Series Designator:**

Unc single mounting facility

## Terminal Type And Quantity:

8 pin all functions

# NSN 5945-00-823-3056

Electromagnetic Relay - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300

