NSN 5945-00-824-5848

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-824-5848

Overall Length:

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility

Overall Height:

1.500 inches

Overall Width:

2.250 inches

Environmental Protection:

Dustproof

Unthreaded Mounting Hole Diameter:

0.201 inches single mounting facility

Contact Surface Treatment:

Rhodium plated

Winding Quantity:

Coil Quantity:

Winding Dc Resistance Rating:

2.4 kilohms third winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Magnetic shield and polarized

Mounting Facility Pattern:

Four position rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

32.5 amperes dc second winding

Operating Voltage Rating And Type At Specificationified Temp:

22.0 volts dc 25 degrees celsius third winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

250.0 ac

Precious Material And Location:

Contact surface rhodium

NSN 5945-00-824-5848

Reed Relay - Page 2 of 2



	ous		

Rhodium

Terminal Type And Quantity:

6 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300