NSN 5945-00-824-8846

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-824-8846

| · |
|---|
| Thread Class: |
| 2a single mounting facility |
| Overall Length: |
| 3.840 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.250 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.750 inches single mounting facility |
| Overall Height: |
| 2.340 inches |
| Overall Width: |
| 1.340 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 2 |
| Winding Dc Resistance Rating: |
| 1.52 kilohms second winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 threaded stud single mounting facility |
| Features Provided: |
| Polarized and latching contacts |
| Thread Size: |
| 0.164 inches single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Operating Current Rating And Type: |
| 50.0 milliamperes dc first winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 50.0 volts dc 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 3.00 amperes dc inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 50.0 dc |
| Thread Series Designator: |
| Unc single mounting facility |

N/a

Shelf Life:

NSN 5945-00-824-8846

Electromagnetic Relay - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300