NSN 5945-00-827-5722

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-827-5722

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 3.310 inches |
| Overall Height: |
| 3.620 inches |
| Overall Width: |
| 2.750 inches |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 24 single mounting facility |
| Thread Size: |
| 0.190 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, single throw, normally open, momentary action |
| Operating Current Rating And Type: |
| 220.0 milliamperes ac single winding |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 3.312 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 110.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 15.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 110.0 ac |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 10 pin all functions |
| Shelf Life: |
| N/a |

NSN 5945-00-827-5722

Electromagnetic Relay - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A03300