

View Online at <https://aerobasegroup.com/nsn/5945-00-827-7216>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.938 inches single mounting facility

**Overall Height:**

3.469 inches

**Overall Width:**

1.438 inches

**Case Material:**

Metal

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

1.3 kilohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 threaded stud single mounting facility

**Pile-up Main Contact Form Arrangement:**

3c

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Cubic Measure:**

8.106 cubic inches

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Time Delay:**

0.02 seconds fixed operate and release time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.187 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

48.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

500.0 milliamperes ac resistive load and 500.0 milliamperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

120.0 ac and 48.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

11 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A03300