NSN 5945-00-828-5477

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-828-5477

| Thread Class: | | | | | | |
|---|--|--|--|--|--|--|
| 2b power takeoff facility hole | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | | | | | | |
| 1.062 inches | | | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | | | | | | |
| 1.062 inches | | | | | | |
| Case Material: | | | | | | |
| Steel | | | | | | |
| Case Surface Treatment: | | | | | | |
| Nickel | | | | | | |
| Environmental Protection: | | | | | | |
| Any acceptable | | | | | | |
| Unthreaded Mounting Hole Diameter: | | | | | | |
| 0.125 inches | | | | | | |
| Magnetic Coil Quantity: | | | | | | |
| 1 | | | | | | |
| Voltage Rating In Volts: | | | | | | |
| 30.0 dc | | | | | | |
| Mounting Facility Type And Quantity: | | | | | | |
| 4 unthreaded hole | | | | | | |
| Current Rating: | | | | | | |
| 1.0 amperes | | | | | | |
| Thready Qty Per Inch (tpi): | | | | | | |
| 40 power takeoff facility hole | | | | | | |
| Actuator Stroke Type: | | | | | | |
| Pull | | | | | | |
| Linear Force Delivered: | | | | | | |
| 2.25 pounds | | | | | | |
| Power Takeoff Connection Type: | | | | | | |
| Internal threads | | | | | | |
| Energizing Stroke Maximum Length: | | | | | | |
| 0.156 inches | | | | | | |
| Thread Size: | | | | | | |
| 0.112 inches power takeoff facility hole | | | | | | |
| Mounting Facility Pattern: | | | | | | |
| Four position rectangular | | | | | | |
| Thread Series Designator: | | | | | | |
| Unc power takeoff facility hole | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 2 threaded stud | | | | | | |
| Shelf Life: | | | | | | |

N/a

NSN 5945-00-828-5477

Electrical Solenoid - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A134a0