NSN 5945-00-828-6528

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-828-6528					
Thread Class:					
2a single mounting facility					
Thread Direction:					
Right-hand single mounting facility					
Overall Length:					
1.531 inches					
Center To Center Distance Between Mounting Facilities Parallel To Length:					
1.187 inches single mounting facility					
Center To Center Distance Between Mounting Facilities Parallel To Width:					
1.187 inches single mounting facility					
Overall Height:					
2.749 inches					
Overall Width:					
1.531 inches					
Case Material:					
Metal					
Environmental Protection:					
Hermetic					
Fragility Factor:					
Moderately rugged					
Winding Quantity:					
1					
Purpose For Which Designed:					
General					
Coil Quantity:					
1					
Duty Type:					
Continuous					
Arc Quenching Method:					
Air					
Mounting Facility Type And Quantity:					
4 threaded stud single mounting facility					
Storage Type:					
General purpose warehouse					
Cubic Measure:					
6.443 cubic inches					
Thready Qty Per Inch (tpi):					
32 single mounting facility					
Thread Size:					
0.138 inches single mounting facility					

Mounting Facility Pattern:
Rectangular single mounting facility

NSN 5945-00-828-6528

Electromagnetic Relay - Page 2 of 2



Nο	nnile-un	Main	Contact	Arranc	ement.
10	IIDIIC-UD	IVICILI	Contact	Allanc	icilicili.

4 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 wire lead all functions

Specification Data:

96906-ms25272 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.