NSN 5945-00-834-9096

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-834-9096

| Overall Length: |
|---|
| 4.690 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.125 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.000 inches single mounting facility |
| Overall Height: |
| 4.310 inches |
| Overall Width: |
| 3.750 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.220 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 1.23 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Diagonal single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 4 pole, single throw, normally open, momentary action |
| Operating Current Rating And Type: |
| 90.0 milliamperes dc single winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 15.0 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 440.0 ac |
| Terminal Type And Quantity: |
| 10 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5945-00-834-9096

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300