NSN 5945-00-839-7515

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-839-7515

g
Overall Length:
3.220 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.491 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.375 inches single mounting facility
Overall Height:
2.210 inches
Overall Width:
1.827 inches
Unthreaded Mounting Hole Diameter:
0.156 inches single mounting facility
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Winding Dc Resistance Rating:
230.0 ohms all windings
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Cubic Measure:
13.001 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonnile-un Main Contact Arrangement

Operating Current Rating And Type:

4 pole, double throw, one position momentary

104.0 milliamperes dc all windings

NSN 5945-00-839-7515

Electromagnetic Relay - Page 2 of 2



Time Delay:
0.025 seconds fixed operate time
Operating Voltage Rating And Type At Specificationified Temp:
24.0 volts dc 25 degrees celsius all windings
Main Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
120.0 ac
Precious Material And Location:
Contacts silver
Precious Material:
Silver
Terminal Type And Quantity:
16 tab, solder lug all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A03300