## NSN 5945-00-839-9077

Electrical Solenoid - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-839-9077

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 1.375 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.375 inches  |
| Case Material:  |
| Any acceptable  |
| Case Surface Treatment:   |
| Any acceptable  |
| Environmental Protection:   |
| Watertight  |
| Unthreaded Mounting Hole Diameter:  |
| 0.265 inches  |
| Magnetic Coil Quantity:   |
| 1   |
| Voltage Rating In Volts:  |
| 30.0 dc   |
| Mounting Facility Type And Quantity:                                      |
| 4 unthreaded hole   |
| Current Rating:   |
| 1.500 amperes   |
| Actuator Stroke Type:   |
| Pull  |
| Linear Force Delivered:   |
| 6.00 pounds   |
| Power Takeoff Connection Type:  |
| Internal plunger  |
| Energizing Stroke Maximum Length:   |
| 0.093 inches  |
| Mounting Facility Pattern:  |
| Four position rectangular   |
| Terminal Type And Quantity:   |
| 2 wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| Δ13420  |