NSN 5945-00-841-4925

Electromagnetic Relay - Page 1 of 2

Unc single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-841-4925

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| 2.380 inches |
| Overall Height: |
| 1.380 inches |
| Overall Width: |
| 1.560 inches |
| Environmental Protection: |
| Hermetic |
| End Application: |
| Type no. An/usd-1 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 120.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Time Delay: |
| 10.00 seconds fixed operate time |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.187 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 22.5 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.5 dc |
| Thread Series Designator: |

NSN 5945-00-841-4925

Electromagnetic Relay - Page 2 of 2



| ī | ermina | ı | Type | Δnd | Qua | antity. |
|---|----------|----|------|------|-----|----------|
| ı | CHILLING | 41 | INDE | Allu | wu | aiititv. |

5 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300