NSN 5945-00-841-9013

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-841-9013
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.020 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.488 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.220 inches single mounting facility
Overall Height:
0.735 inches
Overall Width:
0.790 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
600.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 threaded stud single mounting facility
Storage Type:
General purpose warehouse

Cubic Measure: 0.592 cubic inches

NSN 5945-00-841-9013

Electromagnetic Relay - Page 2 of 2



Thready Qty Per Inch (tpi):
40 single mounting facility
Thread Size:
0.112 inches single mounting facility
Mounting Facility Pattern:
Diagonal single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
21.0 milliamperes dc single winding
Time Delay:
0.005 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
26.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac resistive load and 2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Precious Material And Location:
Contacts silver and contact surfaces gold
Precious Material:
Silver and gold
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
8 wire hook all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300