## NSN 5945-00-842-1386

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-842-1386

Thread Class:
2a single mounting facility
Overall Length:
2.560 inches
Overall Height:
1.620 inches
Overall Width:
1.440 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
300.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Pile-up Main Contact Form Arrangement:
2a
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Operating Current Rating And Type:
Operating Current Rating And Type: 30.0 milliamperes dc single winding
30.0 milliamperes dc single winding
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp: 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts: 115.0 ac  Thread Series Designator:
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  Unc single mounting facility
30.0 milliamperes dc single winding  Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:  1.190 inches single mounting facility  Operating Voltage Rating And Type At Specificationified Temp:  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage:  10.0 amperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:  115.0 ac  Thread Series Designator:  Unc single mounting facility  Terminal Type And Quantity:

## NSN 5945-00-842-1386

Electromagnetic Relay - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A03300