# NSN 5945-00-842-6646

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-842-6646

## Overall Length:

1.360 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches single mounting facility

### **Overall Height:**

0.392 inches

#### **Overall Width:**

1.020 inches

#### **Case Material:**

Metal

#### **Environmental Protection:**

Hermetic

#### **Unthreaded Mounting Hole Diameter:**

0.125 inches single mounting facility

#### **Fragility Factor:**

## Moderately rugged

Contact Material:

#### Silver

**Contact Surface Treatment:** 

Gold

#### Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

552.0 ohms single winding

### Duty Type:

Continuous

#### Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

## Storage Type:

General purpose warehouse

## Cubic Measure:

0.543 cubic inches

## Mounting Facility Pattern:

In-line single mounting facility

# Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

# NSN 5945-00-842-6646

Electromagnetic Relay - Page 2 of 2



**Time Delay:** 0.005 seconds fixed operate and release time **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 2.0 amperes ac resistive load and 2.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver and contact surfaces gold **Precious Material:** Silver and gold **Terminal Type And Quantity:** 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300