## NSN 5945-00-843-4724

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-843-4724

**Thread Class:** 2a single mounting facility **Overall Length:** 1.970 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.437 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.375 inches single mounting facility **Overall Height:** 3.250 inches **Overall Width:** 1.970 inches **Environmental Protection:** Hermetic Winding Quantity: **Coil Quantity:** Winding Dc Resistance Rating: 1.0 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 4 threaded stud single mounting facility **Pile-up Main Contact Form Arrangement:** 2c Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Mounting Facility Pattern:** Rectangular single mounting facility **Operating Current Rating And Type:** 150.0 milliamperes dc single winding Time Delay: 0.01 seconds adjustable release time and 0.02 seconds adjustable release time Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.437 inches single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 150.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 300.0 milliamperes dc resistive load

## NSN 5945-00-843-4724

Electromagnetic Relay - Page 2 of 2



## Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 120.0 dc

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

8 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300