NSN 5945-00-850-0320

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-850-0320 |
|---|
| Overall Length: |
| 1.060 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.062 inches single mounting facility |
| Overall Height: |
| 0.420 inches |
| Overall Width: |
| 0.790 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.122 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 600.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Inert gas |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 2c |
| Features Provided: |
| Polarized and arc quenching |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Time Delay: |
| 0.009 seconds fixed operate and release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Terminal Type And Quantity: |
| 8 pin all functions |

N/a

Shelf Life:

NSN 5945-00-850-0320

Electromagnetic Relay - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A03300