

View Online at <https://aerobasegroup.com/nsn/5945-00-851-7911>

**Overall Length:**

7.500 inches

**Overall Height:**

4.090 inches

**Overall Width:**

3.870 inches

**Unthreaded Mounting Hole Diameter:**

0.144 inches single mounting facility

**End Application:**

Air route surveillane radar (arsr-1), fa-7168 modulator cabinet; arsr-2, fa-7111

**Frequency In Hertz:**

60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

50.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 unthreaded hole single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Operating Current Rating And Type:**

700.0 milliamperes ac single winding

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

5.250 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac

**Special Features:**

Spdt contacts rated 10 amps, 115vac, 115v 50 ohm coil; function: relay, armature (dummy load/amplitron); reference data: k-7403, instruction book, arsr-1 d/e/f, vol 5, sec 10, pg 10-740-1; k-7403, instruction book, arsr-2, vol 5, sec 10, pg 10-546, (fa-7111)

**Terminal Type And Quantity:**

2 tab, solder lug energizing element

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300