

View Online at <https://aerobasegroup.com/nsn/5945-00-851-7911>

Overall Length:

7.500 inches

Overall Height:

4.090 inches

Overall Width:

3.870 inches

Unthreaded Mounting Hole Diameter:

0.144 inches single mounting facility

End Application:

Air route surveillane radar (arsr-1), fa-7168 modulator cabinet; arsr-2, fa-7111

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

50.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Operating Current Rating And Type:

700.0 milliamperes ac single winding

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

5.250 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac

Special Features:

Spdt contacts rated 10 amps, 115vac, 115v 50 ohm coil; function: relay, armature (dummy load/amplitron); reference data: k-7403, instruction book, arsr-1 d/e/f, vol 5, sec 10, pg 10-740-1; k-7403, instruction book, arsr-2, vol 5, sec 10, pg 10-546, (fa-7111)

Terminal Type And Quantity:

2 tab, solder lug energizing element

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300