## NSN 5945-00-852-0663

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-852-0663

| ·····  |
|--|
| Body Style:  |
| Cylindrical frame  |
| Body Diameter:   |
| 1.875 inches   |
| Case Material:   |
| Metal  |
| Case Surface Treatment:                                      |
| Nickel   |
| Environmental Protection:                                    |
| Any acceptable   |
| Connector Manufacturer Code:                                 |
| 99699  |
| Connector Manufacturer Part Number:                          |
| Dh 02-10sl-4p-001  |
| Maximum Operating Temp:                                      |
| 275.0 degrees fahrenheit                                     |
| Inclosure Type:  |
| Hermetically sealed  |
| Magnetic Coil Quantity:                                      |
| 1  |
| Duty Type:   |
| Continuous   |
| Terminal Location:   |
| End opposite actuator  |
| Voltage Rating In Volts:                                     |
| 30.0 dc  |
| Mounting Facility Type And Quantity:                         |
| 1 terminal   |
| Current Rating:  |
| 1.200 amperes  |
| Actuator Stroke Type:  |
| Pull   |
| Linear Force Delivered:                                      |
| 9.00 pounds  |
| Power Takeoff Connection Type:                               |
| Internal plunger   |
| Energizing Stroke Maximum Length:                            |
| 0.095 inches   |
| Special Features:  |
| Surface treatment document and classification: damil-c-26074 |
| Surface Treatment Specification:                             |
|  |

Mil-c-26074 military specification single treatment response

## NSN 5945-00-852-0663

Electrical Solenoid - Page 2 of 2



## Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0

## Mil-std (military Standard):

Mil-c-26074 spec.