NSN 5945-00-856-5073

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-856-5073

| Overall | Length: |
|---------|---------|
|---------|---------|

4.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility

Overall Height:

4.000 inches

Overall Width:

4.000 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.196 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

36.0 ohms all windings

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Latching contacts

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

2.0 amperes dc all windings

Time Delay:

3.00 minutes fixed operate time

Nonpile-up Auxiliary Contact Arrangement:

1 pole, single throw, normally open, momentary action

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

600.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

29.0 dc

NSN 5945-00-856-5073

Electromagnetic Relay - Page 2 of 2



| Terminal Type A | and Quantity | / : |
|-----------------|--------------|------------|
|-----------------|--------------|------------|

10 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300