## NSN 5945-00-856-6596

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-856-6596

| Overall Length:   |
|---|
| 1.380 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.062 inches single mounting facility                                     |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.281 inches single mounting facility                                     |
| Overall Height:   |
| 1.080 inches  |
| Overall Width:  |
| 0.400 inches  |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:  |
| 0.125 inches single mounting facility                                     |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 600.0 ohms single winding   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 4 threaded stud single mounting facility                                  |
| Mounting Facility Pattern:  |
| Rectangular single mounting facility                                      |
| Nonpile-up Main Contact Arrangement:                                      |
| 2 pole, double throw, one position momentary                              |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 26.0 volts dc 25 degrees celsius single winding                           |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 2.0 amperes dc resistive load   |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 28.0 dc   |
| Terminal Type And Quantity:   |
| 8 pin all functions   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5945-00-856-6596

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300