NSN 5945-00-856-7482

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-856-7482

| · |
|---|
| Overall Length: |
| 2.400 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.437 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.875 inches single mounting facility |
| Overall Height: |
| 1.230 inches |
| Overall Width: |
| 1.750 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.156 inches single mounting facility |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 2 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 5.5 kilohms all windings |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 8c |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius all windings |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 3.0 amperes ac resistive load and 3.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 32.0 dc |
| Terminal Type And Quantity: |
| 26 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5945-00-856-7482

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300