## NSN 5945-00-864-4737

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-864-4737             |
|---------------------------------------------------------------------------|
| Overall Length:                                                           |
| 0.870 inches                                                              |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.488 inches single mounting facility                                     |
| Overall Height:                                                           |
| 0.600 inches                                                              |
| Overall Width:                                                            |
| 0.790 inches                                                              |
| Environmental Protection:                                                 |
| Hermetic                                                                  |
| Unthreaded Mounting Hole Diameter:                                        |
| 0.220 inches single mounting facility                                     |
| Winding Quantity:                                                         |
| 1                                                                         |
| Coil Quantity:                                                            |
| 1                                                                         |
| Winding Dc Resistance Rating:                                             |
| 552.0 ohms single winding                                                 |
| Duty Type:                                                                |
| Intermittent                                                              |
| Mounting Facility Type And Quantity:                                      |
| 2 unthreaded hole single mounting facility                                |
| Features Provided:                                                        |
| Latching contacts                                                         |
| Mounting Facility Pattern:                                                |
| In-line single mounting facility                                          |
| Nonpile-up Main Contact Arrangement:                                      |
| 1 pole, double throw, one position momentary                              |
| Time Delay:                                                               |
| 0.004 seconds fixed operate time                                          |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 26.5 volts dc 25 degrees celsius single winding                           |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 2.0 amperes ac resistive load and 2.0 amperes dc resistive load           |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 115.0 ac and 24.0 dc                                                      |
| Terminal Type And Quantity:                                               |
| 5 pin all functions                                                       |
| Fsc Application Data (non-core):                                          |
| Armatures, relay, airborne                                                |
| Shelf Life:                                                               |

N/a

## NSN 5945-00-864-4737

Electromagnetic Relay - Page 2 of 2



|  | Of |  |  |  |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A03300