## NSN 5945-00-866-2488

Thermal Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-866-2488

Overall Length:2.375 inchesOverall Height:1.000 inchesOverall Width:1.375 inchesContact Arrangement:Single pole, single throw, normally openMounting Facility Type And Quantity:2 unthreaded holeContact Maximum Voltage Rating In Volts:115.0 ac and 32.0 dcContact Maximum Current Rating In Amps:6.0 ac or 1.0 dcHeater Voltage Rating In Volts:20.0Delay Time In Seconds:5.0 fixed operateShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:Lunct	Overall Length
Overall Height: 1.000 inches Overall Width: 1.375 inches Contact Arrangement: Single pole, single throw, normally open Mounting Facility Type And Quantity: 2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	-
1.000 inches Overall Width: 1.375 inches Contact Arrangement: Single pole, single throw, normally open Mounting Facility Type And Quantity: 2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No	
Overall Width: 1.375 inches Contact Arrangement: Single pole, single throw, normally open Mounting Facility Type And Quantity: 2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Overall Height:
1.375 inches Contact Arrangement: Single pole, single throw, normally open Mounting Facility Type And Quantity: 2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 115.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	1.000 inches
Contact Arrangement: Single pole, single throw, normally open Mounting Facility Type And Quantity: 2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Overall Width:
Single pole, single throw, normally open Mounting Facility Type And Quantity: 2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	1.375 inches
Mounting Facility Type And Quantity: 2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Contact Arrangement:
2 unthreaded hole Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Single pole, single throw, normally open
Contact Maximum Voltage Rating In Volts: 115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Mounting Facility Type And Quantity:
115.0 ac and 32.0 dc Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	2 unthreaded hole
Contact Maximum Current Rating In Amps: 6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Contact Maximum Voltage Rating In Volts:
6.0 ac or 1.0 dc Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	115.0 ac and 32.0 dc
Heater Voltage Rating In Volts: 20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Contact Maximum Current Rating In Amps:
20.0 Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	6.0 ac or 1.0 dc
Delay Time In Seconds: 5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Heater Voltage Rating In Volts:
5.0 fixed operate Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	20.0
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Delay Time In Seconds:
N/a Unit Of Measure:  Demilitarization: No Fiig:	5.0 fixed operate
Unit Of Measure:  Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
	Fiig:
A50010	