

View Online at <https://aerobasegroup.com/nsn/5945-00-872-4344>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

1.550 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.750 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.562 inches single mounting facility

**Overall Height:**

0.765 inches

**Overall Width:**

1.075 inches

**Case Material:**

Metal

**Environmental Protection:**

Hermetic and shock resistant and vibration resistant

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

300.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 threaded stud single mounting facility

**Cubic Measure:**

1.274 cubic inches

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Mounting Facility Pattern:**

Diagonal single mounting facility

**Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

**Time Delay:**

0.007 seconds fixed operate and release time

**Operating Voltage Rating And Type At Specificationified Temp:**

26.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

110.0 ac and 28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

8 wire hook all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300