NSN 5945-00-872-4344

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-872-4344

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

1.550 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.562 inches single mounting facility

Overall Height:

0.765 inches

Overall Width:

1.075 inches

Case Material:

Metal

Environmental Protection:

Hermetic and shock resistant and vibration resistant

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

300.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Cubic Measure:

1.274 cubic inches

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.007 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.0 volts dc 25 degrees celsius single winding

NSN 5945-00-872-4344

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 10.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 110.0 ac and 28.0 dc **Thread Series Designator:** Unc single mounting facility Terminal Type And Quantity: 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A03300