## NSN 5945-00-879-8600

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-879-8600             |
|---|
| Overall Length:   |
| 1.750 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.500 inches single mounting facility                                     |
| Overall Height:   |
| 0.800 inches  |
| Overall Width:  |
| 0.870 inches  |
| Environmental Protection:   |
| Hermetic  |
| Unthreaded Mounting Hole Diameter:  |
| 0.128 inches single mounting facility                                     |
| Winding Quantity:   |
| 1   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 309.0 ohms single winding   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 2 unthreaded hole single mounting facility                                |
| Pile-up Main Contact Form Arrangement:                                    |
| 6c  |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Operating Current Rating And Type:  |
| 80.0 milliamperes dc single winding                                       |
| Time Delay:   |
| 0.008 seconds fixed operate time  |
| Auxiliary Contact Maximum Voltage Rating In Volts:                        |
| 115.0 ac  |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 26.5 volts dc 25 degrees celsius single winding                           |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 1.0 amperes ac resistive load   |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 115.0 ac  |
| Terminal Type And Quantity:   |
| 20 pin all functions  |

N/a

Shelf Life:

## NSN 5945-00-879-8600

Electromagnetic Relay - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A03300