

View Online at <https://aerobasegroup.com/nsn/5945-00-880-5163>

Thread Class:

2a power takeoff facility stud

Body Style:

Cylindrical frame

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.062 inches

Body Diameter:

0.780 inches

Body Length:

2.010 inches

Case Material:

Metal

Case Surface Treatment:

Nickel

Environmental Protection:

Any acceptable

Unthreaded Mounting Hole Diameter:

0.101 inches

Maximum Operating Temp:

90.0 degrees celsius

Mounting Base Width:

1.320 inches

Actuator Length:

0.625 inches

Actuator Diameter:

0.112 inches

Frequency In Hertz:

400.0

Inclosure Type:

Fully enclosed

Magnetic Coil Quantity:

1

Duty Type:

Continuous

Terminal Location:

Circumference

Voltage Rating In Volts:

115.0 ac

Mounting Facility Type And Quantity:

3 unthreaded hole

Current Rating:

210.0 milliamperes

Thready Qty Per Inch (tpi):

40 power takeoff facility stud

Actuator Stroke Type:

Push

Linear Force Delivered:

4.00 ounces

Power Takeoff Connection Type:

External threads

Energizing Stroke Maximum Length:

0.150 inches

Thread Size:

0.112 inches power takeoff facility stud

Mounting Facility Pattern:

Isosceles triangle

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.531 inches

Thread Series Designator:

Unc power takeoff facility stud

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A134a0