NSN 5945-00-880-5426

Electromagnetic Relay - Page 1 of 2

1.406 inches single mounting facility

Overall Length: 1.720 inches



View Online at https://aerobasegroup.com/nsn/5945-00-880-5426

Center To Center Distance Between Mounting Facilities Parallel To Length:

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches single mounting facility
Overall Height:
1.738 inches
Overall Width:
1.000 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
150.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
4 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
2.989 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
4 pole, double throw, one position momentary

NSN 5945-00-880-5426

Electromagnetic Relay - Page 2 of 2



Operating Current Rating And Type:

80.0 milliamperes dc single winding

Time Delay:

0.007 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 10.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

14 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300