## NSN 5945-00-884-0640

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-884-0640

view crimine at imper/acressacting control which were to do do i of
Terminal Quantity:
2
Terminal Type:
Threaded stud
Mounting Flange Width:
Between 3.937 inches and 4.243 inches
Case Material:
Plastic
Environmental Protection:
Dustproof
Mounting Configuration:
Four no. 6-32 mtg studs on 3.000 by 3.500 mtg centers
Voltage Rating:
300.0 volts
Main Contact Arrangement:
1 pole, single throw, normally open, momentary action
Main Contact Current Type:
Dc
Main Contact Current Rating:
25.0 milliamperes
Meter Movement Current Type:
Ac
Meter Movement Voltage In Volts:
85.000
Meter Movement Current Range:
+0.0/+5000.0 microamperes
Meter Movement Frequency Rating:
60.0 hertz
Meter Mounting Type:
Flush
Contact Closing Condition:
Increase value
Reset Facility Feature:
Provided
Lock In Device Type:
Supplementary locking coil
Release Method:
Manual
Meter Depth Behind Mounting Flange:
1.094 inches
Meter Body Diameter:
2.844 inches

## NSN 5945-00-884-0640

Meter Movement Relay - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T142-k