NSN 5945-00-884-0640

Meter Movement Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-884-0640

| view crimine at imper/acressacting control which were to do do i of |
|---|
| Terminal Quantity: |
| 2 |
| Terminal Type: |
| Threaded stud |
| Mounting Flange Width: |
| Between 3.937 inches and 4.243 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Mounting Configuration: |
| Four no. 6-32 mtg studs on 3.000 by 3.500 mtg centers |
| Voltage Rating: |
| 300.0 volts |
| Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Main Contact Current Type: |
| Dc |
| Main Contact Current Rating: |
| 25.0 milliamperes |
| Meter Movement Current Type: |
| Ac |
| Meter Movement Voltage In Volts: |
| 85.000 |
| Meter Movement Current Range: |
| +0.0/+5000.0 microamperes |
| Meter Movement Frequency Rating: |
| 60.0 hertz |
| Meter Mounting Type: |
| Flush |
| Contact Closing Condition: |
| Increase value |
| Reset Facility Feature: |
| Provided |
| Lock In Device Type: |
| Supplementary locking coil |
| Release Method: |
| Manual |
| Meter Depth Behind Mounting Flange: |
| 1.094 inches |
| Meter Body Diameter: |
| 2.844 inches |

NSN 5945-00-884-0640

Meter Movement Relay - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T142-k