NSN 5945-00-886-1733



Meter Movement Relay - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-00-886-1733 **Terminal Quantity: Terminal Type:** Plain stud **Scale Division Quantity:** 50 **Case Material:** Metal **Environmental Protection:** Dustproof and watertight **Mounting Configuration:** Three 0.125 in. Diameter holes spaced 120 degrees apart on 1.450 in. Radius **Voltage Rating:** 120.0 volts **Main Contact Arrangement:** 1 pole, single throw, both positions maintained **Main Contact Current Type:** Dc **Main Contact Current Rating:** 100.0 milliamperes **Meter Movement Current Type:** Dc **Meter Movement Voltage In Volts:** 0.100 **Meter Movement Current Range:** +0.0/+50.0 microamperes **Meter Mounting Type:** Flush **Contact Closing Condition:** Increase value

Reset Facility Feature:

Provided

Lock In Device Type:

Permanent magnet

Release Method:

Electromagnetic

Mounting Flange Diameter:

Between 3.235 inches and 3.265 inches

Meter Body Diameter:

Between 2.550 inches and 2.570 inches

Meter Depth To Mounting Flange:

Between 1.328 inches and 1.358 inches

NSN 5945-00-886-1733

Meter Movement Relay - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T142-k