NSN 5945-00-887-7918

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-887-7918

| Overall Length: |
|---|
| 6.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 5.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 4.000 inches single mounting facility |
| Overall Height: |
| 7.000 inches |
| Overall Width: |
| 4.625 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.190 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, double throw, one position momentary |
| Nonpile-up Auxiliary Contact Arrangement: |
| 6 pole, single throw, normally open, momentary action and 6 pole, single throw, normally closed, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 250.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 200.0 ac |
| Special Features: |
| Cann0n connector no. 501 for auxiliary contacts |
| Terminal Type And Quantity: |
| 9 threaded stud contacts |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5945-00-887-7918

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300