NSN 5945-00-889-1462

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-889-1462

Thread Class: 2a single mounting facility **Overall Length:** 1.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.982 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 0.982 inches single mounting facility **Overall Height:** 2.000 inches **Overall Width:** 1.000 inches **Environmental Protection:** Hermetic **End Application:** Type no. Mk-666/aas-14 **Winding Quantity:** 1 **Coil Quantity:** Winding Dc Resistance Rating: 12.0 kilohms single winding **Duty Type:** Continuous **Mounting Facility Type And Quantity:** 2 threaded stud single mounting facility **Features Provided:** Polarized Thready Qty Per Inch (tpi): 40 single mounting facility **Thread Size:** 0.112 inches single mounting facility **Mounting Facility Pattern:** Diagonal single mounting facility **Nonpile-up Main Contact Arrangement:** 1 pole, double throw, one position momentary **Operating Current Rating And Type:** 1.3 milliamperes dc single winding

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

Operating Voltage Rating And Type At Specificationified Temp:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

NSN 5945-00-889-1462

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:	Main	Contact	Maximum	Voltage	Rating	In	Volts:
---	------	---------	---------	---------	--------	----	--------

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

5 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03300