NSN 5945-00-889-9948

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-889-9948

| Thread Class: |
|---|
| 2b mounting facility hole |
| Body Style: |
| Cylindrical frame |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.187 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.000 inches |
| Body Length: |
| 4.030 inches |
| Case Material: |
| Steel |
| Case Surface Treatment: |
| Cadmium |
| Environmental Protection: |
| Dustproof and explosion proof |
| Fragility Factor: |
| Moderately rugged |
| Inclosure Type: |
| Fully enclosed |
| |
| Magnetic Coil Quantity: |
| Magnetic Coil Quantity: 1 |
| |
| 1 |
| 1 Duty Type: |
| 1 Duty Type: Continuous |
| 1 Duty Type: Continuous Terminal Location: |
| Duty Type: Continuous Terminal Location: Circumference |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type: |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type: Pull |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type: Pull Linear Force Delivered: |
| Duty Type: Continuous Terminal Location: Circumference Voltage Rating In Volts: 28.0 dc Mounting Facility Type And Quantity: 4 threaded hole Current Rating: 4.4 amperes Storage Type: General purpose warehouse Actuator Stroke Type: Pull Linear Force Delivered: 4.50 pounds |

0.375 inches

NSN 5945-00-889-9948

Electrical Solenoid - Page 2 of 2



Power Takeoff Connection Hole Diameter:

Between 0.100 inches and 0.106 inches

Thread Size:

0.190 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular

Thread Series Designator:

Unf mounting facility hole

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A134a0